

**Amendments to the Claims**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of claims:**

1. (currently amended) A raise bore drilling and lining apparatus for creation of a borehole comprising:

a raise boring drill for boring a raise into a pilot hole using a drill string to create a bore hole; a reamer head affixed to one end of said drill string[[, and]] ~~a spreader assembly affixed to said reamer head~~ for distributing a liner material on the wall of said bore hole during operation of said reamer head; ~~said assembly affixed to said reamer head~~, and a material supply connected to said spreader assembly to supply lining said liner material to said spreader assembly. thereto.

2. (original) Apparatus according to claim 1 wherein said material supply includes a duct extending axially along said drill string.

3. (original) Apparatus according to claim 2 wherein said spreader assembly includes a plate rotatable relative to said reamer head.

4. (original) Apparatus according to claim 3 wherein said plate is rotatable by a motor located within said spreader assembly.

5. (currently amended) Apparatus according to claim 4 wherein said motor is driven by fluid supplied through said [[drive]] drill string.

6. (original) Apparatus according to claim 5 wherein said liner material is supplied by a pair of ducts, each carrying a respective component of said liner material.

7. (original) Apparatus according to claim 6 wherein each of said ducts is connected to a respective reservoir within said spreader assembly.

8. (original) Apparatus according to claim 7 wherein said reservoirs are connected to respective

pipes to deliver material within said reservoir to said plate.

9. (currently amended) A reamer assembly for use with a raise bore drilling and lining apparatus, said reamer assembly including a reamer head, a spreader assembly secured to said reamer head for movement therewith and for distributing a liner material on the wall of said bore hole during operation thereof, and a material supply connected to said spreader assembly to deliver material ~~to said spreader assembly. thereto.~~

10. (currently amended) A reamer assembly according to claim 9 wherein said spreader assembly includes a plate rotatable relative to said reamer head to dispense said liner material.

11. (currently amended) A reamer assembly according to claim 10 ~~wherein~~ including a motor ~~[[rotate]]~~ for rotating said plate.

12. (original) A reamer assembly according to claim 11 wherein said motor is fluid driven.

13. (original) A reamer assembly according to claim 10 including a material reservoir and supply pipes extending from said reservoir to deliver material to said plate.

14. (original) A reamer assembly according to claim 13 including a pair of reservoirs, each having respective supply pipes.

15. (currently amended) A drill rod comprising an outer casing, a connection at opposite ends of said rod to permit ~~said rods~~ a plurality of said drill rod to be connected in seriatim ~~[[into]]~~ to form a drill string; and a liner located within said casing, said liner having a plurality of concentric ~~[[tubes]]~~ walls ~~[[each]]~~ defining a series of fluid passageway ~~passageways between successive ones of said walls~~ to convey fluid axially within said rod ~~from one end to another. between said opposite ends.~~

16. (currently amended) A drill rod according to claim 15 wherein said ~~[[tubes]]~~ walls are supported at axially spaced intervals within said casing.

17. (original) A drill rod according to claim 16 wherein said liner is supported radially and axially within said casing.

18. (currently amended) A method of drilling and lining a raise bore hole comprising the steps of:

- (a) boring a pilot hole with a pilot bit secured to a drill string;
- (b) replacing said pilot bit with a reamer assembly including a spreader[[,]] assembly to dispense distribute lining material;
- (c) reaming said pilot hole for a specified distance to create a bore hole by moving said reamer assembly axially in a first direction whilst rotating said drill string;
- (d) moving said reamer assembly in an opposite axial direction to said first direction; and
- (e) applying a liner ~~medium~~ material to the wall of said bore hole using said spreader assembly whilst moving said reamer assembly axially in said first direction.

19. (original) The method of claim 18 including repeating steps (c), (d), and (e) until the desired length of bore hole has been created.

20. (currently amended) The method of claim 19 including the step of supplying said liner ~~medium~~ material through a duct within said drill string.

21. (original) The method of claim 20 including the step of flushing said duct between repetitions of steps (c), (d), and (e).